



// BULK FOOD



760LA	Bulk food delivery 5 bar (75 psi) - FDA.....	83
760LB	Bulk food delivery 5 bar (75 psi) - FDA.....	83
720LA	Bulk food S&D 10 bar (150 psi) - FDA.....	84
720LG	Bulk food S&D 10 bar (150 psi) - FDA.....	84
967OE	Fish handling - PVC - Super elastic.....	85
949AA	Fish pump 3 bar (45 psi).....	85

Dimensions shown may be changed without prior notice

// 760LA

**Bulk food delivery 5 bar (75 psi)
FDA****Tube:** white NR - abrasion resistant.**Reinforcement:** high tensile textile cords - antistatic wire.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk food and material delivery. Specially designed for grain, flour and plastic pellets transfer.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
75,0	3"	93,00	3,66	5	75	15	225				2,370	1,60
90,0	3 1/2"	102,00	4,02	5	75	15	225				2,120	1,43
100,0	4"	120,00	4,72	5	75	15	225				3,550	2,39
102,0	4"	120,00	4,72	5	75	15	225				3,170	2,14
110,0	4 5/16"	122,00	4,80	5	75	15	225				2,540	1,71

83

INDUSTRIAL HOSE

// 760LB

**Bulk food delivery 5 bar (75 psi)
FDA****Tube:** white NR - abrasion resistant.**Reinforcement:** high tensile textile cords - antistatic wire.**Cover:** grey SBR/EPDM - abrasion and ozone resistant.**Application:** bulk food and material delivery. Specially designed for grain, flour and plastic pellets transfer.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
102,0	4"	118,00	4,65	5	75	15	225				3,140	2,12

// 720LA



**Bulk food S&D 10 bar (150 psi)
FDA**

Tube: white NR - abrasion resistant.
Reinforcement: high tensile textile cords with embedded steel helix wire - antistatic wire.
Cover: black conductive SBR/NR - abrasion and ozone resistant.
Application: bulk food and material suction and delivery. Specially designed for grain, flour and plastic pellets transfer.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
76,0	3"	92,00	3,62	10	150	30	450	228,0	8,98	90	2,680	1,81
90,0	3 1/2"	106,00	4,17	10	150	30	450	270,0	10,63	90	3,330	2,24
102,0	4"	118,00	4,65	10	150	30	450	306,0	12,05	90	3,700	2,49

// 720LG



**Bulk food S&D 10 bar (150 psi)
FDA**

Tube: white NR - abrasion resistant.
Reinforcement: high tensile textile cords with embedded steel helix wire - antistatic wire.
Cover: green NBR/PVC - abrasion and ozone resistant.
Application: bulk food and material suction and delivery. Specially designed for grain, flour and plastic pellets transfer.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	67,00	2,64	10	150	30	450	153,0	6,02	100	1,830	1,23
76,0	3"	92,00	3,62	10	150	30	450	228,0	8,98	90	2,840	1,91
102,0	4"	118,00	4,65	10	150	30	450	306,0	12,05	90	3,910	2,63
127,0	5"	145,00	5,71	5	75	15	225	508,0	20,00	80	5,680	3,82
152,0	6"	170,00	6,69	5	75	15	225	608,0	23,94	80	7,050	4,74
203,0	8"	223,00	8,78	5	75	15	225	812,0	31,97	70	10,470	7,04

Dimensions shown may be changed without prior notice

// 9670E

**Fish handling - PVC - Super elastic****Construction:** transparent PVC - abrasion and ozone resistant.**Reinforcement:** light blue shock resistant rigid PVC.**Application:** fish transfer on fish farms.**Constant operation:** -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↻		↻		⤴		↺	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
152,0	6"			2	30	6	90	380,0	14,96	95	5,600	3,77
203,0	8"			2	30	6	90	609,0	23,98	95	9,200	6,19
254,0	10"			2	30	6	90	1016,0	40,00	95	14,500	9,75
305,0	12"			1	15	3	45	1525,0	60,04	95	19,000	12,77

85

INDUSTRIAL HOSE

// 949AA

**Fish pump 3 bar (45 psi)****Tube:** black NBR - oil, abrasion and sea water resistant.**Reinforcement:** high tensile textile cords.**Cover:** black conductive CR - oil, abrasion, ozone and sea water resistant.**Application:** fish transfer from fishing net to ship deck.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		↺	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
254,0	10"	262,00	10,31	3	45	10	150				4,800	3,23
305,0	12"	313,00	12,32	3	45	10	150				5,740	3,86
355,0	14"	367,00	14,45	3	45	10	150				9,020	6,07
406,0	16"	418,00	16,46	3	45	10	150				10,890	7,32
457,0	18"	469,00	18,46	3	45	10	150				12,380	8,32
508,0	20"	522,00	20,55	3	45	10	150				14,330	9,64