



// FIRE FIGHTING



283AA	Fire reel 12 bar (180 psi) - EN 694/A2.....	54
251AA	Fire reel 40 bar (600 psi) - Textile braided - NF EN 1947/C/1/II.....	54
212AA	Fire engine water S&D 5 bar (75 psi) - NF EN ISO 14557/A.....	54

// 283AA



**Fire reel 12 bar (180 psi)
EN 694/A2**

Tube: black synthetic elastomer.
Reinforcement: high tensile textile cords.
Cover: black synthetic elastomer - abrasion and ozone resistant.
Application: fire reels.
Constant operation: -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↻		↻		⤴		⚡		📦	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
25,0	1"	34,00	1,34	12	180	48	720	200,0	7,87		0,570	0,39	

// 251AA



**Fire reel 40 bar (600 psi) - Textile braided
NF EN 1947/C/1/II**

Tube: black SBR.
Reinforcement: high tensile textile braids.
Cover: black SBR - abrasion and ozone resistant.
Application: hose reels on fire fighting vehicles.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚡		📦	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
25,0	1"	36,00	1,42	40	600	120	1750	100,0	3,94		0,620	0,42	

// 212AA



**Fire engine water S&D 5 bar (75 psi)
NF EN ISO 14557/A**

Tube: black SBR.
Reinforcement: high tensile textile cords with embedded steel helix wire.
Cover: black SBR - abrasion and ozone resistant.
Application: water suction and delivery on fire fighting vehicles.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚡		📦	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
45,0	1 3/4"	55,00	2,17	5	75	15	225	180,0	7,09	100	1,510	1,02	
70,0	2 3/4"	82,00	3,23	5	75	15	225	280,0	11,02	90	2,760	1,86	
110,0	4 5/16"	122,00	4,80	5	75	15	225	440,0	17,32	80	4,710	3,17	