



// HOT AIR



952AA	Hot air blower 10 bar (150 psi) - Soft wall - External textile braid.....	31
962LA	Hot air blower 10 bar (150 psi) - Soft wall.....	31
902AA	Hot air blower 10 bar (150 psi) - Hard wall.....	32
902AE	Hot air blower 10 bar (150 psi) - Hard wall.....	32
902LE	Hot air blower 10 bar (150 psi) - Hard wall.....	33
903LE	Hot air blower 10 bar (150 psi) - Hard wall - FDA.....	33

Dimensions shown may be changed without prior notice

// 952AA

**Hot air blower 10 bar (150 psi) - Soft wall - External textile braid****Tube:** black EPDM - heat resistant.**Reinforcement:** high tensile textile braids.**Application:** hot air connection from volumetric compressor to bulk food/material road tanker.**Constant operation:** -40 °C +180 °C (-40 °F +356 °F)

↔		↔		↕		↕		⤴		%		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in		kg/m	lb/ft	
51,0	2"	67,00	2,64	10	150	30	450	255,0	10,04		1,580	1,07	
76,0	3"	92,00	3,62	10	150	30	450	380,0	14,96		2,340	1,58	

// 962LA

**Hot air blower 10 bar (150 psi) - Soft wall****Tube:** white EPDM - heat resistant.**Reinforcement:** high tensile textile cords.**Cover:** black EPDM - heat, abrasion and ozone resistant.**Application:** hot air connection from volumetric compressor to bulk food/material road tanker.**Constant operation:** -40 °C +180 °C (-40 °F +356 °F)

↔		↔		↕		↕		⤴		%		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in		kg/m	lb/ft	
51,0	2"	69,00	2,72	10	150	30	450	306,0	12,05		2,580	1,74	
76,0	3"	94,00	3,70	10	150	30	450	456,0	17,95		3,490	2,35	

// 902AA



Hot air blower 10 bar (150 psi) - Hard wall

Tube: black EPDM - heat resistant.
Reinforcement: high tensile textile cords with embedded steel helix wire.
Cover: black EPDM - heat, abrasion and ozone resistant.
Application: hot air connection from volumetric compressor to bulk food/material road tanker. Special light weight and flexible construction.
Constant operation: -40 °C +180 °C (-40 °F +356 °F)

↔		↔		↻		↻		⤴		⚖	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	63,00	2,48	10	150	30	450	153,0	6,02	100	1,510	1,02
63,0	2 1/2"	77,00	3,03	10	150	30	450	189,0	7,44	100	2,000	1,35
76,0	3"	90,00	3,54	10	150	30	450	228,0	8,98	90	2,400	1,62
102,0	4"	116,00	4,57	10	150	30	450	306,0	12,05	90	3,330	2,24

// 902AE



Hot air blower 10 bar (150 psi) - Hard wall

Tube: black EPDM - heat resistant.
Reinforcement: high tensile textile cords with embedded steel helix wire.
Cover: blue EPDM - heat, abrasion and ozone resistant.
Application: hot air connection from volumetric compressor to bulk food/material road tanker. Special light weight and flexible construction.
Constant operation: -40 °C +180 °C (-40 °F +356 °F)

↔		↔		↻		↻		⤴		⚖	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
76,0	3"	90,00	3,54	10	150	30	450	228,0	8,98	90	2,310	1,56

Dimensions shown may be changed without prior notice

// 902LE

**Hot air blower 10 bar (150 psi) - Hard wall****Tube:** white EPDM - heat resistant.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** blue EPDM - heat, abrasion and ozone resistant.**Application:** hot air connection from volumetric compressor to bulk food/material road tanker. Special light weight and flexible construction.**Constant operation:** -40 °C +180 °C (-40 °F +356 °F)

↔		↔		↻		↻		⤴		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	63,00	2,48	10	150	30	450	153,0	6,02	100	1,560	1,05
53,0	2 1/16"	65,00	2,56	10	150	30	450	159,0	6,26	100	1,610	1,09
63,0	2 1/2"	77,00	3,03	10	150	30	450	189,0	7,44	90	2,380	1,60
76,0	3"	90,00	3,54	10	150	30	450	228,0	8,98	90	2,840	1,91
90,0	3 1/2"	104,00	4,09	10	150	30	450	270,0	10,63	90	3,520	2,37

33

INDUSTRIAL HOSE

// 903LE

**Hot air blower 10 bar (150 psi) - Hard wall FDA****Tube:** white EPDM - heat resistant.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** blue EPDM - heat, abrasion and ozone resistant.**Application:** hot air connection from volumetric compressor to bulk food/material road tanker. Special light weight and flexible construction.**Constant operation:** -40 °C +180 °C (-40 °F +356 °F)

↔		↔		↻		↻		⤴		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
38,0	1 1/2"	50,00	1,97	10	150	30	450	114,0	4,49	100	1,140	0,77
51,0	2"	63,00	2,48	10	150	30	450	153,0	6,02	100	1,470	0,99
76,0	3"	90,00	3,54	10	150	30	450	228,0	8,98	90	2,670	1,80
102,0	4"	116,00	4,57	10	150	30	450	306,0	12,05	90	3,630	2,44
127,0	5"	145,00	5,71	10	150	30	450	445,0	17,52	80	6,060	4,08