



// PLASTER



764OL	Plaster conveyance - Polyurethane.....	94
752AA	Plaster 10 bar (150 psi).....	94
757AA	Plaster 40 bar (600 psi).....	94
758AA	Plaster 55 bar (800 psi).....	95
758AE	Plaster 55 bar (800 psi).....	95

// 7640L



Plaster conveyance - Polyurethane

Construction: transparent polyurethane - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: pneumatic conveyance of pre-mixed synthetic plaster from silo to plaster pumping machine. Assembly complete with fittings also available.

Constant operation: -20 °C +60 °C (-4 °F +140 °F)

↔		↔		↙		↘		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
45,0	1 3/4"							203,0	7,99	60	0,680	0,46

// 752AA



Plaster 10 bar (150 psi)

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: black SBR/NR - abrasion and ozone resistant - pin pricked.

Application: plaster and sand/cement mix pumping. Also suitable for heavy duty sandblast.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↙		↘		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
60,0	2 3/8"	80,00	3,15	10	150	30	450				2,310	1,56
65,0	2 9/16"	85,00	3,35	10	150	30	450				2,520	1,70
90,0	3 1/2"	113,00	4,45	10	150	30	450				4,110	2,77
102,0	4"	127,00	5,00	10	150	30	450				4,680	3,15

// 757AA



Plaster 40 bar (600 psi)

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: black SBR/NR - abrasion and ozone resistant - pin pricked.

Application: plaster pumping.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↙		↘		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"	38,00	1,50	40	600	100	1500				0,700	0,48
32,0	1 1/4"	46,00	1,81	40	600	100	1500				0,870	0,59
35,0	1 3/8"	49,00	1,93	40	600	100	1500				0,960	0,65
38,0	1 1/2"	54,00	2,13	40	600	100	1500				1,190	0,80
51,0	2"	67,00	2,64	40	600	100	1500				1,600	1,08

Dimensions shown may be changed without prior notice

// 758AA



Plaster 55 bar (800 psi)

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: black SBR/NR - abrasion and ozone resistant - pin pricked.

Application: plaster pumping.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"	40,00	1,57	55	800	140	2000				0,870	0,59
32,0	1 1/4"	49,00	1,93	55	800	140	2000				1,250	0,85
38,0	1 1/2"	58,00	2,28	55	800	140	2000				1,710	1,15
51,0	2"	71,00	2,80	55	800	110	1600				2,220	1,50

// 758AE



Plaster 55 bar (800 psi)

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: blue SBR/EPDM - abrasion and ozone resistant.

Application: plaster pumping.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"	40,00	1,57	55	800	140	2000				0,940	0,64
32,0	1 1/4"	49,00	1,93	55	800	140	2000				1,450	0,98
38,0	1 1/2"	58,00	2,28	55	800	140	2000				1,990	1,34
51,0	2"	71,00	2,80	55	800	110	1600				2,570	1,73