



// SANDBLAST



753AA	Sandblast 12 bar (180 psi) - Premium quality.....	91
753AH	Sandblast 12 bar (180 psi) - Premium quality.....	91
753AG	Sandblast 12 bar (180 psi) - Premium quality.....	92
755AA	Sandblast 12 bar (180 psi) - Top quality.....	92

Dimensions shown may be changed without prior notice

// 753AA



Sandblast 12 bar (180 psi) - Premium quality

Tube: black conductive NR - abrasion resistance 50 mm³ (ISO 4649/A).

Reinforcement: high tensile textile cords.

Cover: black SBR/NR - abrasion and ozone resistant - pin pricked.

Application: abrasive material blasting. Designed for long service life in heavy duty applications.

Constant operation: -40 °C +80 °C (-40 °F +176 °F)

↻		↻		↻		↻		↻		↻		↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
13,0	1/2"	27,00	1,06	12	180	36	540				0,540	0,37	
19,0	3/4"	33,00	1,30	12	180	36	540				0,700	0,48	
19,0	3/4"	38,00	1,50	12	180	36	540				0,990	0,67	
19,0	3/4"	40,00	1,57	12	180	36	540				1,150	0,78	
25,0	1"	39,00	1,54	12	180	36	540				0,860	0,58	
25,0	1"	48,00	1,89	12	180	36	540				1,520	1,03	
32,0	1 1/4"	48,00	1,89	12	180	36	540				1,220	0,82	
32,0	1 1/4"	55,00	2,17	12	180	36	540				1,810	1,22	
38,0	1 1/2"	55,00	2,17	12	180	36	540				1,630	1,10	
38,0	1 1/2"	60,00	2,36	12	180	36	540				2,050	1,38	
51,0	2"	71,00	2,80	12	180	36	540				2,380	1,60	
51,0	2"	71,00	2,80	12	180	36	540				2,380	1,60	
51,0	2"	73,00	2,87	12	180	36	540				2,640	1,78	
51,0	2"	76,00	2,99	12	180	36	540				2,910	1,96	
51,0	2"	76,00	2,99	12	180	36	540				2,910	1,96	

// 753AH



Sandblast 12 bar (180 psi) - Premium quality

Tube: black conductive NR - abrasion resistance 50 mm³ (ISO 4649/A).

Reinforcement: high tensile textile cords.

Cover: red SBR/EPDM - abrasion and ozone resistant - pin pricked.

Application: abrasive material blasting. Designed for long service life in heavy duty applications.

Constant operation: -40 °C +80 °C (-40 °F +176 °F)

↻		↻		↻		↻		↻		↻		↻	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
13,0	1/2"	27,00	1,06	12	180	36	540				0,540	0,37	
19,0	3/4"	33,00	1,30	12	180	36	540				0,700	0,48	
25,0	1"	39,00	1,54	12	180	36	540				0,860	0,58	
32,0	1 1/4"	48,00	1,89	12	180	36	540				1,220	0,82	
38,0	1 1/2"	55,00	2,17	12	180	36	540				1,630	1,10	
51,0	2"	71,00	2,80	12	180	36	540				2,380	1,60	

// 753AG



Sandblast 12 bar (180 psi) - Premium quality

Tube: black conductive NR - abrasion resistance 50 mm³ (ISO 4649/A).

Reinforcement: high tensile textile cords.

Cover: green SBR/EPDM - abrasion and ozone resistant - pin pricked.

Application: abrasive material blasting. Designed for long service life in heavy duty applications.

Constant operation: -40 °C +80 °C (-40 °F +176 °F)

				◆		◆				△		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	38,00	1,50	12	180	36	540				0,970	0,66
25,0	1"	48,00	1,89	12	180	36	540				1,500	1,01
32,0	1 1/4"	55,00	2,17	12	180	36	540				1,790	1,21
38,0	1 1/2"	60,00	2,36	12	180	36	540				1,790	1,21

// 755AA



Sandblast 12 bar (180 psi) - Top quality

Tube: black conductive NR - abrasion resistance 36 mm³ (ISO 4649/A).

Reinforcement: high tensile textile cords.

Cover: black SBR/NR - abrasion and ozone resistant - pin pricked.

Application: abrasive material blasting. Designed for long service life in heavy duty application.

Constant operation: -40 °C +80 °C (-40 °F +176 °F)

↔		↔		●		●		⤴		⚙		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
19,0	3/4"	33,00	1,30	12	180	36	540				0,740	0,50	
19,0	3/4"	33,00	1,30	18	270	54					0,740	0,50	
25,0	1"	39,00	1,54	12	180	36	540				0,910	0,62	
32,0	1 1/4"	48,00	1,89	12	180	36	540				1,280	0,87	
32,0	1 1/4"	48,00	1,89	18	270	54					1,280	0,87	
38,0	1 1/2"	55,00	2,17	12	180	36	540				1,470	0,99	
38,0	1 1/2"	55,00	2,17	18	270	54					1,470	0,99	
51,0	2"	71,00	2,80	12	180	36	540				2,430	1,64	
51,0	2"	71,00	2,80	12	180	36	540				2,430	1,64	